
2024 Ambient Air Monitoring Annual Network Plan and SO₂ Data Requirement Rule Annual Report

June 24, 2024



West Virginia Department of Environmental Protection
Division of Air Quality
601 57th Street, SE.
Charleston, WV 25304
304-926-0499

Executive Summary

The Annual Network Plan (ANP) provides information on each site within the West Virginia Department of Environmental Protection Division of Air Quality's (DAQ's) ambient air quality network. The requirement for this ANP was established by the United States Environmental Protection Agency (EPA) in 40 CFR Part 58.

Appendix A to this document provides DAQ's Sulfur Dioxide Data Requirements Rule (SO₂ DRR) Annual Report, including an emissions assessment, pursuant to the requirements of 40 CFR 51, Subpart BB, at §51.1205(b).

A public inspection and comment period is open for 30 days from the date this document is posted on our website.

A summary of air monitoring network changes and updates since the previous approval includes:

- Per the provisions of §58.11(e), DAQ requests exclusion of Federal Equivalent Method (FEM) PM_{2.5} data for National Ambient Air Quality Standards (NAAQS) determination at all sites with Federal Reference Method (FRM) PM_{2.5} data; requests EPA discontinue the practice of substituting FEM data on non-FRM days; requests EPA correct historical data using this practice; and requests EPA update historical and current design value (DV) calculations accordingly.

NCore (54-039-0020) – The results from EPA's FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool for 2021-2023 can be found in Appendix B. While the results fall within EPA's acceptance criteria, we request that EPA use only the FRM data at this site and discontinue the practice of substituting FEM data on non-FRM days.

Moundsville (54-051-1002) – EPA Region 3 has concurred the 2021-2023 FEM data from the continuous FEM PM_{2.5} T640x should be excluded from NAAQS determinations. The on-site FRM data will continue to be used for NAAQS determination without data substitution. The results from EPA's FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool for 2021-2023 can be found in Appendix B. The EPA-approved firmware corrections software was installed on December 1, 2023.

- As approved in advance by EPA Region 3, the air monitoring shelter at **Morgantown Airport (54-061-0003)** was moved within the airport perimeter on November 28-29, 2023 to allow them to construct a new car wash building. The new location for the shelter is further from the roadway and has easier access for operators.
- Teledyne API T640X continuous PM_{2.5} monitors, with the EPA-approved firmware correction software installed, began reporting PM_{2.5} data to AirNow on December 1, 2023, and AQS on January 1, 2024, at the following sites:
 - o **Huntington/Prindle Field (54-011-0007)**
 - o **Summit Circle (54-029-0009)**
 - o **Marland Heights (54-009-0011)**

- EPA Region 3 conducted a Technical Systems Audit in August 2023.
 - EPA Region 3 recommended the **Fairmont (54-049-0006)** and **Clarksburg (054-033-0003)** sites be relocated to remove them from rooftop locations. We are actively searching for new locations that allow us to maintain DV, meet EPA siting requirements and EPA approval, and have property owners amenable to working with WVDEP to enter into a lease agreement.
 - Another rooftop site is located in **South Charleston (054-039-1005)** and we may request EPA approval to move this site if an alternate location can be identified that allows us to maintain DV, meets EPA siting requirements and EPA approval, and has property owners amenable to working with WVDEP to enter into a lease agreement.
- After consultation with EPA Region 3, the following single-pollutant sites, which only monitored SO₂, were shutdown, since they were well below the federal (NAAQS) and are represented by other monitors in the network:
 - **Lawrenceville (54-029-0015)**– last single-point quality control check July 6, 2023
 - **New Cumberland (54-029-0007)**– last single-point quality control check July 6, 2023
 - **McKim Ridge (054-009-0007)**– last single-point quality control check January 4, 2024

On June 28, 2023, EPA Region 3 approved the discontinuation of the non-SIP related SO₂ monitors in Hancock County: **Lawrenceville (54-029-0015)** and **New Cumberland/ (54-029-0007)**.

On January 8, 2024, EPA Region 3 approved the discontinuation of operations of the McKims Ridge SO₂ only site since there are two others in the area to fulfill SO₂ SIP monitoring requirements.

Appendix C provides a summary of monitored SO₂ concentrations in Brooke and Hancock Counties

- DAQ plans to consolidate the remaining two air monitoring sites in Brooke County, WV – **Follansbee (54-009-0005)** and **Marland Heights (54-009-0011)**.
 - These sites are within four (4) air-miles of one another
 - Consultation with EPA Region 3 indicates this plan is acceptable, pending final advance approval from EPA Region 3 of the consolidated location, once it has been identified.
 - The remaining SO₂ monitor will fulfill the SO₂ SIP monitoring requirement.
 - A continuous PM₁₀ monitor will remain in the geographic area through the end of the second 10-year maintenance period of the PM₁₀ SIP in 2026.

Appendix C provides a summary of monitored SO₂ concentrations in Brooke and Hancock Counties.

- As of March 2024, all sites in the state with continuous SO₂ and O₃ monitors are operating with automatic weekly zero/span/precision quality control checks.

Purpose

The Annual Network Plan (ANP) provides information on permanent air monitors within the West Virginia Department of Environmental Protection Division of Air Quality's (DAQ's) State or Local Air Monitoring Stations (SLAMS) ambient air quality network. The primary purpose of SLAMS is for NAAQS comparison.

If necessary, the ANP includes documentation of any changes to the state's PM_{2.5} monitoring that would affect the location of a violating PM_{2.5} monitor. It should be noted that there are no PM_{2.5} monitors in West Virginia that currently violate the 24-hour NAAQS. DAQ will be evaluating PM_{2.5} monitoring results with respect to the new annual PM_{2.5} NAAQS promulgated in 2024.

Except for circumstances not anticipated during this review period, such as inadequate federal or state funding, leasing issues, site maintenance issues, personnel resource issues or equipment failures, no other *intentional* changes are expected to be made to the PM_{2.5} FRM monitoring network or the criteria pollutant monitoring network/stations during the next 12 months except those discussed within this document. With the exception of the Follansbee site, all monitoring sites are leased and those leases are subject to periodic renewals which can affect the DAQ's ability to retain a monitoring site location. The proposed changes are listed in the specific air monitoring site section.

In the pages that follow, each individual monitoring site and corresponding photograph, is listed by county along with the Air Quality Subsystem (AQS) site ID number, site location information, the Metropolitan Statistical Area (MSA) that is represented by the site, a statement as to whether it meets the requirements of Part 58, sampling and analytical method for each parameter, proposed site changes, and any other general comments regarding the site. Other pertinent information such as latitude/longitude, site purpose, the monitor's objective/site type and representative scale is also listed for each site.

Background

On October 17, 2006, the US Environmental Protection Agency (EPA) published final amendments to 40 CFR Part 53 and 58 "Revisions to Ambient Air Monitoring Regulations; Final Rule". This rule became effective on December 18, 2006.

Under Part 58, Subpart B-Monitoring Network, § 58.10 Annual Monitoring Network Plan and Periodic Assessments (a)(1): "Beginning July 1, 2007, the State, or where applicable local, agency shall adopt and submit to the Regional Administrator an annual monitoring network plan which shall provide for the establishment and maintenance of an air quality surveillance system that consists of a network of SLAMS monitoring stations including FRM, FEM, and ARM monitors that are part of SLAMS, NCore stations, STN stations, State speciation stations, SPM stations, and/or, in serious, severe and extreme ozone nonattainment areas, PAMS stations, and SPM monitoring stations. The plan shall include a statement of purposes for each monitor and evidence that siting and operation of each monitor meets the requirements of appendices A, C, D, and E of this part, where applicable. The annual monitoring network plan must be made available for public inspection for at least 30 days prior to submission to EPA."

On March 28, 2016 (effective April 27, 2016) EPA finalized revisions to 40CFR Part 58 "Revision to Ambient Monitoring Quality Assurance and Other Requirements; Final Rule".

Under Part 58 §58.10 (a)(1) “Annual monitoring network plan and periodic network assessment” EPA amended the 2006 language to clarify the handling of any public comment received on the plan: “The annual monitoring network plan must be made available for public inspection and comment for at least 30 days prior to submission to the EPA *and the submitted plan shall include and address, as appropriate, any received comments* (emphasis added).

To review the September 2006 and April 2016 Monitoring Regulations please visit <https://www.epa.gov/amtic/monitoring-regulations>.

Additional information and to view data publicly available from the AQS data system can be found at www.epa.gov/airdata/ . A copy of the latest DAQ annual air monitoring report can be found at <https://dep.wv.gov/daq/air-monitoring/Pages/default.aspx>

SO₂ Data Requirement Rule (DRR)


On August 10, 2015, EPA finalized requirements for air agencies to monitor or model ambient sulfur dioxide (SO₂) levels in areas with large sources of SO₂ emissions to help implement the 1-hour SO₂ National Air Ambient Quality Standard (NAAQS). The rule establishes that, at a minimum, air agencies must characterize air quality around sources which emit 2,000 tons per year (tpy) or more of actual SO₂ emissions. An air agency may avoid the requirement for air quality characterization near a source by adopting enforceable emission limits which ensure that the source will not emit more than 2,000 tpy maximum potential to emit of SO₂. The rule requires agencies to use either modeling of actual source emissions or appropriately sited ambient air quality monitors to assess local SO₂ concentrations.

As stated in previous ANPs, there are no West Virginia sources subject to the DRR rule which elected to conduct ambient air monitoring for SO₂. However, there is currently one DRR ambient SO₂ monitoring site in Mason County, West Virginia, near the Ohio border. Two sources in Ohio – the Gavin Power, LLC James M. Gavin power plant and the Ohio Valley Electric Corporation Kyger Creek power plant – began conducting air monitoring under the SO₂ DRR in 2017. One of these monitoring sites is located in Lakin, West Virginia. Both facilities are electric generating utilities and are located within two miles of each other along the Ohio River in Gallia County, Ohio. The Ohio Environmental Protection Agency (OEPA) is the Primary Quality Assurance Organization (PQAO). DAQ is not responsible for the operation, maintenance, data collection, reporting or quality assurance activities at this site. Additional details may be found in the specific West Virginia counties sections of this report.

Appendix A to this document provides DAQ’s SO₂ DRR Annual Report, including an emissions assessment, pursuant to the requirements of 40 CFR 51, Subpart BB, at §51.1205(b).

This ANP covers operations during 2023 as well as proposed changes for 2024. The map below shows all known air quality monitoring sites in West Virginia using FRM/FEM monitors. WVDEP-DAQ operates 14 sites across the state, as shown on the map.

Air Monitoring Sites in West Virginia



The table below provides summary information on all of DAQ's air monitoring sites. DAQ currently operates 14 sites across the state.

West Virginia Division of Air Quality - Monitoring Network

As of 4/4/2024

County/Location	AQ5 ID	Pollutants Monitored											AQ5 Latitude	AQ5 Longitude
		AIR TOXICS	PM10-2.5	PM10 T640X	PM2.5 FRM	PM2.5 Cont.	PM2.5 SPEC	CO	SO2	O3	NOx	MET		
Berkeley														
Martinsburg/Ball Field (MT)	540030003				X					X			39.448001	-77.964130
Brooke														
Follansbee/Mahan Lane (F1)	540090005				X				X				40.340933	-80.596533
Weirton/Mariand Heights (W5)	540090011			X	X	X			X				40.394583	-80.612017
Cabell														
Huntington/Prindle Field (H3)	540110007				X	X				X			38.410242	-82.432436
Greenbrier														
Sam Black Church/DOH Garage (SB)	540250003									X			37.908533	-80.632633
Hancock														
Weirton/Summit Circle (W3)	540290009			X	X	X			X	X			40.427372	-80.592318
Harrison														
Clarksburg/Washington Irving JHS (CL)	540330003				X								39.278117	-80.342250
Kanawha														
Charleston Ncore (C8)	540390020	X	X		X	X	X	X	X	X	X	X	38.346258	-81.621161
South Charleston Library (SC)	540391005				X								38.366183	-81.693727
Marion														
Fairmont/Marion Health Care Hosp (FT)	540490006				X								39.481483	-80.134667
Marshall														
Moundsville/Natl Guard Armory (MV)	540511002				X	X	X		X				39.915961	-80.733858
Monongalia														
Morgantown Airport (MA)	540610003				X				X	X			39.649444	-79.920278
Ohio														
Warwood (WD)	540690010	X			X					X			40.114760	-80.700972
Wood														
Vienna/Neale School (V1)	541071002				X				X	X			39.323553	-81.552367
Total Sites	14	2	1	2	13	5	2	1	7	8	1	1		

** PM10-2.5 = Manual 3 day sampler (Charleston NCore)

** T640X = Continuous Particulate samplers

** PM2.5 = Manual 3 day samplers

** FRM = Federal Reference Method

** SPEC = Speciated

** MET = Meteorology

Berkeley County

Site: Martinsburg Ball Field

Location: Martinsburg Ball Field, Charlotte Prather Park, Martinsburg, Berkeley County, WV 25401

AQS ID: 54-003-0003

MSA: Hagerstown-Martinsburg, MD-WV

Latitude: 39.448001

Longitude: -77.96413



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Current site established in 1999 to provide air quality monitoring in Berkeley County and the Eastern Panhandle of WV.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential Lo-Volume sampler, Federal Reference Method, samples once every three days. Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted: 4/13/2023 and 10/10/2023

Gaseous:

Ozone – UV absorption continuous gas monitor operated during ozone season March – October

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 5/25/2023

Brooke County

Site: Mahan Lane

Location: Mahan Lane, Follansbee, Brooke County, WV 26037

AQS ID: 54-009-0005

MSA: Steubenville-Weirton OH-WV

Latitude: 40.340933

Longitude: -80.596533



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. The site was established in 1983 to provide air quality monitoring in an industrialized area of Brooke County. DAQ had some historical leasing issues with this site and currently operates without a lease in place. This site underwent an extensive upgrade in 2019.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential Lo-Volume sampler, Federal Reference Method, samples once every three days. Samples analyzed by gravimetric analysis.

Representative siting scale: Neighborhood

Monitoring objective/site type: Population oriented

State audit conducted 4/10/2023 and 10/11/2023

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Neighborhood

Monitoring objective/site type: Population oriented

State accuracy audit conducted 10/24/2023

Site: McKims Ridge

Location: McKims Ridge Road, Colliers, Brooke County, WV 26035

AQS ID: 54-009-0007

MSA: Steubenville-Weirton OH-WV

Latitude: 40.38966

Longitude: -80.58624



Implemented Change: After consultation with EPA Region 3, this single-pollutant site which only monitored SO₂ was shutdown. The data was well below the federal NAAQS and the area is represented by other monitors in the network. The last single-point quality control check was on January 4, 2024. This shelter has been removed and the lease has been discontinued.

Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1997 as part of a dispersion model evaluation study and to provide additional air quality monitoring in Brooke and Hancock Counties in West Virginia.

Parameters monitored, sampling method, scale, and purpose:

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Neighborhood

Monitoring objective/site type: Population oriented

State accuracy audit conducted 7/7/2023

Site: Marland Heights

Location: Marland Heights, Weirton, Brooke County, WV 26062

AQS ID: 54-009-0011

MSA: Steubenville-Weirton, OH-WV

Latitude: 40.394583

Longitude: -80.612017



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1992 to provide air quality monitoring in an industrial area of Brooke and Hancock Counties in West Virginia.

Implemented Change: This site began reporting continuous PM_{2.5} data from the to AirNow on December 1, 2023, and AQS on January 1, 2024.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

Teledyne API T640x continuous PM₁₀ monitor, Federal Equivalent Method

Representative siting scale: Neighborhood

Monitoring objective/site type: Population oriented

State flow rate audit conducted 4/25/2023 and 9/22/2023

PM_{2.5} sequential Lo-Volume sampler, Federal Reference Method, samples once every three days. A collocated PM_{2.5} monitor samples every 12th day. Samples analyzed by gravimetric analysis.

Representative siting scale: Neighborhood

Monitoring objective/site type: Population oriented

State audit conducted 4/10/2023 and 10/11/2023

Co-located state audit conducted 4/10/2023 and 10/11/2023

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Neighborhood

Monitoring objective/site type: Population oriented

State accuracy audit conducted 3/15/2023

Cabell County

Site: Huntington/ Prindle Field

Location: 1313 14th Street, Huntington, Cabell County, WV 25701

AQS-ID: 54-011-0007

MSA: Huntington-Ashland, WV-KY-OH Metro Area

Latitude: 38.410242

Longitude: -82.432436



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. This site replaces the Marshall University, Huntington site, and started reporting data in 2019.

Implemented Change: This site began reporting continuous PM_{2.5} data from the to AirNow on December 1, 2023, and AQS on January 1, 2024.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential Lo-Volume sampler, Federal Reference Method, samples once every three days. A collocated sequential PM_{2.5} monitor samples every 12th day. Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/19/2023 and 10/31/2023

Co-located state audit conducted 4/19/2023 and 10/31/2023

EPA performance evaluation audit conducted 8/31/2023

Teledyne API T640x continuous PM_{2.5} monitor, Federal Equivalent Method

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/19/20 23 and 10/31/2023

Gaseous:

Ozone – UV absorption continuous gas monitor operated during ozone season March – October

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 9/19/2023

EPA through the probe audit conducted 8/31/2023

Greenbrier County

Site: Sam Black Church

Location: 235 Gray Gables Rd, Crawley, Department of Highway Garage, Greenbrier County, WV 24913

AQS ID: 54-025-0003

MSA: NA

Latitude: 37.908533

Longitude: -80.632633



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Current site established in 1999 to continue historical background ozone air quality monitoring that started in 1984 in Greenbrier County, a rural area of West Virginia. A new shelter was installed, along with upgraded power in early 2019. The shelter was moved within the perimeter of the DOH facility on October 12, 2022 to make way for a new salt shed. It was moved next to an old shelter that has been surplus to DOH for storage.

Parameters monitored, sampling method, scale, and purpose:

Gaseous:

Ozone – UV absorption continuous gas monitor operated during ozone season March – October

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 5/9/2023

Hancock County

Site: New Cumberland

Location: RD#1 Carothers Road, New Cumberland, Hancock County, WV 26047

AQS ID: 54-029-0007

MSA: Steubenville-Weirton, OH-WV

Latitude 40.460138

Longitude -80.576567



Implemented Change: After consultation with EPA Region 3, this single-pollutant site which only monitored SO₂ was shutdown. The data was well below the federal NAAQS and the area is represented by other monitors in the network. The last single-point quality control check was on July 6, 2023. This shelter has been removed and the lease has been discontinued.

Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1990 as part of a multi-state SO₂ study (PA-WV-OH) and to provide air quality monitoring in Hancock County, WV.

Parameters monitored, sampling method, scale, and purpose:

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 3/16/2023

Site: Chester

Location: A.T. Allison Elementary School, 647 Railroad Street, Chester, Hancock County, WV 26034

AQS ID: 54-029-0008

MSA: Steubenville-Weirton, OH-WV

Latitude: 40.615720

Longitude: -80.560000



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. The site at Chester was established on 5/15/1991 to provide air quality monitoring in northern Hancock County, WV. The last data reported to AQS was the SO₂ hourly and 5-minute data through 12/31/2017.

Discretionary special purpose monitoring for the collection of PM₁₀ samples for metals analysis was conducted at this site starting in 2009 (TSP metals, and later PM₁₀ metals) to support EPA's multi-state investigation into manganese emissions from SH Bell in Liverpool, OH. After a period of overlap, monitoring was switched from TSP metals to PM₁₀ metals monitoring in 2016. PM₁₀ samples were collected over a 24-hour period on a once every 6-day schedule.

This discretionary PM₁₀ metals toxics site operated throughout 2019, and discontinued operations at the end of the first quarter of 2020. No pollutants are currently monitored at this site. The shelter became unusable (see photos) and is in the process of being removed.

Implemented Change: This shelter has been removed.

Site: Summit Circle

Location: Summit Circle, Weirton, Hancock County, WV 26062

AQS ID: 54-029-0009

MSA: Steubenville-Weirton, OH-WV

Latitude: 40.427372

Longitude: -80.592318



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1992 to provide air quality monitoring in an industrial area of Hancock County, West Virginia.

As part of an extensive upgrade to this the site, including electrical lines, fencing and decking, and a new shelter, operations were suspended in September 2019, and resumed by early-mid 2020.

Implemented Change: This site began reporting continuous PM_{2.5} data from the to AirNow on December 1, 2023, and AQS on January 1, 2024.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

Teledyne API T640x continuous PM₁₀ monitor, Federal Equivalent Method

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 4/25/2023 and 9/22/2023

PM_{2.5} sequential sampler, Federal Reference Method, samples once every three days.
Samples analyzed by gravimetric analysis.
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State accuracy audit conducted 4/10/2023 and 10/11/2023

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor
Representative siting scale: Neighborhood
Monitoring objective/site type: Population oriented
State accuracy audit conducted 6/13/2023

Ozone – UV absorption continuous gas monitor operated during ozone season Mar – Oct
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State accuracy audit conducted 5/24/2023

Site: Lawrenceville

Location: Lawrenceville Park and Tyrone Road, Lawrenceville, Hancock County, WV 26034

AQS ID: 54-029-0015

MSA: Steubenville-Weirton, OH-WV

Latitude: 40.618353

Longitude: -80.540618



Implemented Change: After consultation with EPA Region 3, this single-pollutant site which only monitored SO₂ was shutdown. The data was well below the federal NAAQS and the area is represented by other monitors in the network. The last single-point quality control check was on July 6, 2023. This shelter has been removed.

Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1995 in response to the 1992 installation of Waste Technology Industries (WTI), now known as Heritage Thermal Services, and to provide air monitoring in upper Hancock County, West Virginia.

Parameters monitored, sampling method, scale, and purpose:

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 7/6/2023

Harrison County

Site: Clarksburg

Location: Washington Irving Middle School, Clarksburg, Harrison County, WV 26301

AQS ID: 54-033-0003

MSA: NA

Latitude: 39.278117

Longitude: -80.342250



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1997 to monitor PM_{2.5} in Harrison County, West Virginia.

Proposed Change: EPA Region 3 recommended this site be relocated to remove it from the current rooftop location. We are actively searching for new locations that allow us to maintain DV, meet EPA siting requirements and EPA approval, and have property owners amenable to working with WVDEP to enter into a lease agreement.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential Lo-Volume sampler, Federal Reference Method, samples once every three days. Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/11/2023 and 10/11/2023

Kanawha County

Site: NCore

Location: 1436 Dixie St., Charleston, Kanawha County, WV 25301

AQS ID: 54-039-0020

MSA: Charleston, WV

Latitude: 38.346258

Longitude: -81.621161



Comment: Site complies with Appendix A, C, D, E of Part 58. Site required to be established by EPA as part of the national NCore multi-pollutant monitoring network. This site started reporting data in 2016.

Requested Change: The results from EPA's FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool for 2021-2023 can be found in Appendix B. While the results fall within EPA's acceptance criteria, we request that EPA use only the FRM data at this site and discontinue the practice of substituting FEM data on non-FRM days.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

Met One BAM 1020 continuous PM_{2.5} monitor

Representative siting scale: Urban

Monitoring objective/site type: Population oriented
State audit conducted 4/24/2023 and 10/23/2023

PM_{2.5} sequential sampler, Federal Reference Method, samples once every three days.
Samples analyzed by gravimetric analysis.
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State audit conducted 4/20/2023 and 10/26/2023
EPA performance evaluation audit conducted 8/31/2023

PM₁₀ sequential sampler, Federal Reference Method, samples once every three days.
Samples analyzed by gravimetric analysis. Data is used only to calculate and report PM
Coarse which equals PM₁₀ minus PM_{2.5}.
Representative siting scale: Urban
Monitoring objective/site type: Population oriented

Gaseous:

Sulfur Dioxide – UV fluorescent continuous trace gas monitor
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State audit conducted 6/8/2023

Ozone – UV absorption continuous trace gas monitor
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State audit conducted 9/26/2023

NO/NO_y – Chemiluminescence continuous trace gas monitor
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State audit conducted – This unit has been out of service since August 2023

Carbon Monoxide – Gas filter correlation continuous trace gas monitor
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State audit conducted 3/29/2023

PM_{2.5} Speciation

Speciation Trends Network (STN) site equipped with Met One Super SASS and URG
3000N Carbon sampler. Both sample on a once every three-day schedule.
Representative siting scale: Urban
Monitoring objective/site type: Population oriented
State flow rate audit conducted 3/30/2023, 6/27/2023, 9/25/2023 and 12/28/2023

Toxics

TSP metals, certain Volatile Organic Compounds, and Carbonyls
Representative siting scale: Neighborhood
Samples once every 12 days
Monitoring objective/site type: Population oriented

Other

Ultra-Sonic wind sensor

Temperature

Barometric Pressure

Relative Humidity

Site: South Charleston

Location: South Charleston Public Library 312 4th Ave., South Charleston, Kanawha County, WV 25303

AQS ID: 54-039-1005

MSA: Charleston, WV

Latitude: 38.366183

Longitude: -81.69372717



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1974 to provide air quality monitoring in Kanawha County, West Virginia.

Proposed Change: We may request EPA approval to move this site if an alternate location can be identified that would allow us to maintain DV, meet EPA siting requirements and EPA approval, and have property owners amenable to working with WVDEP to enter into a lease agreement.

Parameters monitored, sampling method, scale, and purpose:

Particulates

PM_{2.5} sequential Low-Volume sampler, Federal Reference Method. Samples once every three days. Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/20/2023 and 10/26/2023

Marion County

Site: Fairmont

Location: 401 Guffey Street, Manchin Health Care Center, Fairmont, Marion County, WV 26554

AQS ID: 54-049-0006

MSA: NA

Latitude: 39.481483

Longitude: -80.134667



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 2000 to monitor PM_{2.5} in Marion County, West Virginia.

Proposed Change: EPA Region 3 recommended this site be relocated to remove it from the current rooftop location. We are actively searching for new locations that allow us to maintain DV, meet EPA siting requirements and EPA approval, and have property owners amenable to working with WVDEP to enter into a lease agreement.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential sampler, Federal Reference Method, samples once every three days.

Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/11/2023 and 10/11/2023

Marshall County

Site: Moundsville

Location: Moundsville National Guard Armory, Moundsville, Marshall County, WV 26041

AQS ID: 54-051-1002

MSA: Wheeling, WV-OH

Latitude: 39.915961

Longitude: -80.733858



Comment: Site complies with Appendix A, C, D, E of Part. This site is suitable for NAAQS comparisons except for the PM_{2.5} continuous special purpose monitor. Site established in 1983 to provide air quality monitoring in Marshall County, West Virginia.

Implemented change: A continuous PM_{2.5} T640x monitor was installed in 2019; DAQ began reporting quality-assured data from January 1, 2021 to AQS; DAQ began reporting daily to AIRNow on April 21, 2021. The EPA-approved firmware corrections software was installed on December 1, 2023. EPA Region 3 has concurred that the FEM data from 2021-2023 from the continuous FEM PM_{2.5} T640x should be excluded from NAAQS determinations. The on-site FRM data is to continue to be used for NAAQS determination without data substitution. The results from EPA's FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool for 2021-2023 can be found in Appendix B.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential sampler, Federal Reference Method. Samples once every three days.
Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/10/2023 and 10/10/2023

PM_{2.5} Teledyne API T640X continuous PM_{2.5} monitor, Federal Equivalent Method.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented
State audit conducted 4/25/2023 and 9/22/2023

PM_{2.5} Speciation

Chemical Speciation Network site. Met One Super SASS and URG 3000N Carbon sampler. Both sample on a once every six-day schedule

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State flow rate audit conducted 2/13/2023, 6/7/2023, 9/5/2023 and 11/13/2023

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 10/26/2023

Mason County

Site: Lakin

Location: HWY 62, Lakin, WV

AQS ID: 54-053-0001

CBSA: Point Pleasant WV-OH

Latitude: 38.95649

Longitude: -82.08866

Comment: American Electric Powers' (AEP) James M. Gavin and Ohio Valley Electrical Corporation (OVEC) Kyger Creek electric generating facilities located in Gallia County, Ohio have elected to conduct air monitoring under the SO₂ Data Requirements Rule. One of the SO₂ air monitoring sites is in Lakin, Mason County, West Virginia and is included herein for reference. The site is operated by Shell Engineering on behalf of AEP and OVEC. The Ohio Environmental Protection Agency is the responsible Primary Quality Assurance Organization. The DAQ does not have any role in the operation, data reporting, or quality assurance of this site.

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Neighborhood

Monitoring objective/site type: Source-oriented

Monongalia County

Site: Morgantown

Location: Morgantown Municipal Airport, Morgantown, Monongalia County, WV 26505

AQS ID: 54-061-0003

MSA: NA

Latitude: 39.649367

Longitude: -79.920897



Implemented Change: As approved in advance by EPA Region 3, the air monitoring shelter was moved within the Airport perimeter on November 28-29, 2023 to allow them to construct a new car wash building. The new location for the shelter is further from the roadway and has easier access for operators.

Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1983 to provide air quality monitoring in Monongalia County, West Virginia.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential sampler, Federal Reference Method. Samples once every three days.

Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/11/2023 and 10/10/2023

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 9/27/2023

Ozone – UV absorption continuous gas monitor operated during ozone season March – October

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 5/24/2023

Ohio County

Site: Warwood/Wheeling

Location: Warwood Water Treatment Plant, Wheeling, Ohio County, WV 26003

AQS ID: 54-069-0010

MSA: Wheeling, WV-OH

Latitude: 40.11476

Longitude: -80.700972



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Current site established in 2005 to continue to provide air quality monitoring in Ohio County, West Virginia.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential sampler, Federal Reference Method, samples once every three days.

Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/10/2023 and 10/10/2023

Gaseous:

Ozone – UV absorption continuous gas monitor operated during ozone season March – October

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 9/14/2023

Toxics

TSP metals, certain Volatile Organic Compounds, and Carbonyls.

Representative siting scale: Neighborhood

Samples once every 12 days

Monitoring objective/site type: Population oriented

Wood County

Site: Vienna

Location: Neale Elementary School, Vienna, Wood County, WV 26105

AQS ID: 54-107-1002

MSA: Parkersburg-Marietta, WV-OH

Latitude: 39.323553

Longitude: -81.552367



Comment: Site complies with Appendix A, C, D, E of Part 58. This site is suitable for NAAQS comparisons. Site established in 1975 to provide air quality monitoring in Wood County, West Virginia.

Parameters monitored, sampling method, scale, and purpose:

Particulates:

PM_{2.5} sequential sampler, Federal Reference Method. Samples once every three days.

Samples analyzed by gravimetric analysis.

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State audit conducted 4/10/2023 and 10/11/2023

Gaseous:

Sulfur Dioxide – UV fluorescent continuous gas monitor

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 6/15/2023

Ozone – UV absorption continuous gas monitor operated during ozone season March – October

Representative siting scale: Urban

Monitoring objective/site type: Population oriented

State accuracy audit conducted 9/20/2023

Appendix A - SO₂ Data Requirement Rule Annual Report

Introduction

On August 21, 2015, the U.S. Environmental Protection Agency (EPA) published the *Data Requirements Rule for the 2010 1-Hour Sulfur Dioxide (SO₂) Primary National Ambient Air Quality Standard (NAAQS)* (80 FR 51051)¹. This rule, referred to as the Data Requirements Rule (DRR), includes provisions in 40 CFR 51.1205(b) requiring an air agency to submit a report to the EPA documenting SO₂ emissions for areas where modeling of actual SO₂ emissions served as the basis for designating the area attainment for the 2010 1-hour SO₂ NAAQS. The report must include an assessment of the cause of any emission increases from the previous year and a recommendation regarding whether additional modeling is needed. These annual reports are due by July 1 after the effective date of an area's initial designation.

Regulatory History

On June 2, 2010, the EPA signed a final rule (75 FR 35519)² revising the SO₂ NAAQS and established a new 1-hour SO₂ primary NAAQS of 75 parts per billion (ppb), based on the three-year average of the annual 99th percentile of daily 1-hour maximum concentrations. Whenever the EPA revises a NAAQS, the Clean Air Act (CAA) requires the EPA to designate areas as “attainment” (meeting), “nonattainment” (not meeting), or “unclassifiable” (insufficient data). Within one year of a NAAQS revision, each state must submit their designation recommendations. The CAA requires the EPA to complete the designations process within three years of a NAAQS revision.

On August 5, 2013, the EPA published (78 FR 47191)³, a final rule designating 29 areas, in 16 states, including two areas in West Virginia (Steubenville, OH-WV and Marshall, WV), as nonattainment for the 2010 1-hour SO₂ NAAQS. In that rulemaking, the EPA stated the agency would address the designation of all other areas in separate future actions. At that time, the EPA was still developing its strategy for completing the designations process. The EPA anticipated using a hybrid approach, allowing the use of either modeling or monitoring data for designations purposes, but the agency anticipated the need to issue additional rulemaking and guidance documents prior to finalizing additional designations. Shortly thereafter, three lawsuits were filed against the EPA in different U.S. District Courts, alleging the agency had failed to perform a nondiscretionary duty under the CAA by not issuing 1-hour SO₂ designations for all portions of the country within three years of NAAQS promulgation. To resolve the legal challenges, a consent decree was entered in federal court on March 2, 2015.

¹ <https://www.govinfo.gov/content/pkg/FR-2015-08-21/pdf/2015-20367.pdf>

² <https://www.govinfo.gov/content/pkg/FR-2010-06-22/pdf/2010-13947.pdf>

³ <https://www.govinfo.gov/content/pkg/FR-2013-08-05/pdf/2013-18835.pdf>

This consent decree established the criteria and deadlines for the EPA to complete a second, third, and fourth round of designations for the 2010 1-hour SO₂ NAAQS. The second round mostly affected only those areas that contained a source meeting certain emissions-related criterion established in the consent decree. Such areas were required to be designated no later July 2, 2016. The third round affected all undesignated areas that had not deployed a new, operating SO₂ monitoring network by January 1, 2017. The deadline for the third round was December 31, 2017. Most areas in the U.S. were designated in this round. In the fourth and final round, the remaining undesignated areas were to be designated by December 31, 2020.

On August 21, 2015, the consent decree was finalized, and the EPA published the DRR (80 FR 51051)⁴. The primary purpose of the DRR is to require air agencies to characterize maximum 1-hour SO₂ concentrations around sources emitting 2,000 tons per year (tpy) or more of SO₂. Implementation of the DRR requires states to use either modeling or ambient monitoring to assess SO₂ concentrations or to establish federally enforceable emission limits to bind sources to emissions of less than 2,000 tpy.

The initial implementation step of the DRR required states to identify by January 15, 2016, sources not located in a nonattainment area which had actual annual SO₂ emissions of at least 2,000 tons or were deemed by the air agency as requiring further air quality characterization.

The DRR established January 13, 2017, as the deadline for states to submit the results of source modeling. This date also served as the compliance deadline for any new federally enforceable emission limits used to satisfy the DRR. While these deadlines, and those associated with the monitoring option, allow the third and fourth rounds of designations to be informed by data that must be submitted pursuant to the DRR, meeting the second round's July 2, 2016, designation deadline required states and the EPA to take actions before the DRR was finalized.

Effective August 12, 2020, the EPA redesignated the West Virginia portion of the Steubenville, OH-WV area to attainment for the 2010 SO₂ NAAQS (85 FR 41925)⁵. Further, effective November 25, 2020, the EPA redesignated the Marshall, WV area to attainment (85 FR 67661)⁶.

Emissions Assessment

Applicable SO₂ emission sources, defined as having actual annual SO₂ emissions of 2,000 tons or more, were modeled by the Division of Air Quality (DAQ) as the basis for designating the area as attainment with the 2010 1-hour SO₂ NAAQS. The applicable sources modeled were all electrical generating units (EGU). Because emissions were modeled based on actual emissions instead of allowable emissions, §51.1205(b) requires an annual report to be submitted to EPA

⁴ <https://www.govinfo.gov/content/pkg/FR-2015-08-21/pdf/2015-20367.pdf>

⁵ <https://www.govinfo.gov/content/pkg/FR-2020-07-13/pdf/2020-13452.pdf>

⁶ <https://www.govinfo.gov/content/pkg/FR-2020-10-26/pdf/2020-21757.pdf>

documenting the annual SO₂ emissions from each applicable source and providing an assessment of any emission increases from the previous year. Additionally, §51.1205(b)(1) requires an agency’s recommendation regarding whether additional modeling characterizing an area’s air quality is needed to determine whether the area meets or does not meet the 2010 1-hr SO₂ NAAQS.

The DRR requires an assessment of SO₂ emissions increases from the previous year. This report includes certified ambient SO₂ air quality monitoring data for 2023, therefore DAQ is assessing actual SO₂ emissions from the previous year, 2022, that may have impacted the 2023 monitoring data. Assessing only the SO₂ increase from a previous year limits the analysis to a two-year period and does not allow for an accurate assessment to determine the need for additional modeling. A comparison of actual annual SO₂ emissions from each applicable source during the initial modeling period, which demonstrated attainment with the 2010 NAAQS, to the previous year actual emissions allows for a better and more meaningful assessment. Therefore, DAQ has made our assessment based upon the initial modeling years as compared to the previous year. **Table 1** below shows the three-year initial modeling period for each applicable source and the results of that modeling as a maximum percentage of the 2010 1-hour SO₂ NAAQS.

Table 1: EGU Modeled Year and Percent of NAAQS


EGU Modeled	Years Modeled (actual emissions)	Maximum Percent of NAAQS Modeled
Fort Martin	2013-2015	64%
Harrison Power Station	2012-2014	52.8%
John Amos	2013-2015	< 50%
Mountaineer	2012-2014	< 50%
Mount Storm	2013-2015	< 50%
Pleasants Power	2013-2015	77.7%

Figure 1 shows the actual annual SO₂ emissions for each modeled EGU from 2013 through 2023. These emissions were taken from the EPA Clean Air Markets Program Data (CAMPD) database⁷. As the chart illustrates, SO₂ emissions from each EGU have been largely stable or decreasing over the assessment period. As was the case for most facets of the supply and demand network, the global pandemic of 2020 caused some disruptions in the energy sector. Electricity demand and generation were certainly affected. Though most EGUs experienced a slight increase in SO₂ production, Pleasants Power saw a large increase. From 2020 and into 2021, Pleasants Power operated for more hours than in previous years and therefore produced more SO₂. The increase in

⁷ <https://campd.epa.gov/>

operational hours in 2021 over 2020 was common among coal EGUs throughout the country, as frequent spiking and generally rising average natural gas prices⁸ throughout 2021 allowed coal units to be more cost competitive with natural gas units in markets where lowest cost generation assets are dispatched first. The U. S. Energy Information Administration (EIA) reports coal electricity generation in the United States increased from 773 billion kilowatt-hours (kWh) in 2020 to 899 billion kWh in 2021, while natural gas generation decreased from 1,624 billion kWh to 1,575 billion kWh over the same time period⁹. Although the 2023 ambient air data has not been certified at the time of this report, 2023 SO₂ values reported to CAMPD have stabilized to be more in line with pre-COVID values and continue to be less than the highest modeled year.

Figure 1: 2013-2023 EGU SO₂ Emissions in tons



From Figure 1, the highest actual SO₂ emissions from the initial three-year modeling period can be compared to the actual 2023 emissions for each source. Table 2 shows this comparison and demonstrates that actual 2023 SO₂ emissions were less than those of the highest modeled year.

⁸ <https://www.eia.gov/dnav/ng/hist/rngwhhdm.htm>

⁹ <https://www.eia.gov/energyexplained/electricity/electricity-in-the-us.php>

Table 2: Highest Modeled Year SO₂ Emissions vs. 2023 SO₂ Emissions

EGU Modeled	Highest Modeled Year	Highest Modeled Year Emissions (tons)	2023 Emissions (tons)	Change from Highest Modeled Year to 2023 (tons)
Fort Martin	2013	6,767	2,373	-4,394
Harrison	2013	19,266	15,651	-3,615
John Amos	2014	6,172	4,537	-1,635
Mountaineer	2014	4,410	2,805	-1,605
Mount Storm	2015	4,825	2,057	-2,768
Pleasants Power	2013	14,477	6,988	-7,489

Conclusions

As shown in Table 1, emissions initially modeled for each source were substantially less than the SO₂ 1-hour NAAQS, with one-half of the sources modeled less than 50 percent of the standard. The emission comparison in Table 2 demonstrates that 2023 actual SO₂ emissions were less than the emissions for the highest modeled year for all EGUs.

If the 2023 actual SO₂ emissions were modeled, the results would be less than those modeled during the three-year initial modeling period and less than the maximum percent of the NAAQS shown in Table 1 for all EGUs. While still below the highest modeled value, SO₂ emission from Harrison Power Station has increased from pre-pandemic levels. United States Energy Information Administration (USEIA) indicates that Harrison sources the coal used for fuel from the nearby Harrison County Mine, which has been supplying increasingly lower Btu coal with a higher sulfur content. CAMPD data indicates little fluctuation in load and heat input demonstrating consistent electricity demand. For Harrison to maintain this load and heat, they must consume more coal and the higher-sulfur content amplifies SO₂ generation.

With consideration of, and despite recent, unprecedented global events, emissions from these facilities remain below the modeled years and demonstrate a generally stable trend overall. Therefore, as required in §51.1205(b), and based on this assessment, the air quality areas represented by the modeled sources continue to meet the 2010 1-hour SO₂ NAAQS and DAQ recommends no additional modeling is needed to characterize air quality in these areas.


Appendix B – DAQ requests exclusion of FEM PM_{2.5} data for NAAQS determination at all sites with FRM PM_{2.5} data per §58.11(e)

Per §58.11(e), DAQ requests exclusion of FEM PM_{2.5} data for NAAQS determination at all sites with FRM PM_{2.5} data; requests EPA discontinue the practice of substituting FEM data on non-FRM days; requests EPA correct historical data using this practice; and requests EPA update historical and current design value calculations accordingly.


NCore (54-039-0020) – The results from EPA’s FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool for 2021-2023 can be found in Appendix B. While the results fall within EPA’s acceptance criteria, we request that EPA use only the FRM data at this site and discontinue the practice of substituting FEM data on non-FRM days.

Moundsville (54-051-1002) – EPA Region 3 has concurred the 2021-2023 FEM data from the continuous FEM PM_{2.5} T640x should be excluded from NAAQS determinations. The on-site FRM data will continue to be used for NAAQS determination without data substitution. The results from EPA’s FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool for 2021-2023 can be found in Appendix B. The EPA-approved firmware corrections software was installed on December 1, 2023.

Charleston NCore FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool 2021-2023



Moundsville FRM-FEM PM_{2.5} Continuous Monitor Compatibility Assessment Tool 2021-2023



Appendix C Summary of Monitored SO₂ Concentrations Statewide, Including in Brooke and Hancock Counties

The charts and tables in this Appendix provide summarized information on the SO₂ monitors operated by the agency. The monitored concentrations are well below the federal National Ambient Air Quality Standards (NAAQS).

Background

Historically, the Northern Panhandle of WV had many SO₂ sources, as well as monitored and modeled SO₂ NAAQS violations. SIPs and consent orders were developed to address these issues. Due to the installation of control devices, as well as retirement and shutdown of older SO₂-emitting facilities, the ambient air has become much cleaner and the area has been designated by EPA as attaining the SO₂ NAAQS.

Due to the historical source mix, Brooke and Hancock Counties operated a dense SO₂ monitoring network for decades. Currently we are evaluating our network needs with respect to current SO₂ sources in the area, NAAQS and SIPs, as well as resources (both personnel and funding). This evaluation became a priority in 2023 due to potential mold concerns in aging shelters (particularly at the single-pollutant sites that only monitored SO₂), and whether those needed to be budgeted for replacement, or simply decommissioned.

Changes and Plans


- After consultation with EPA Region 3, the following single-pollutant sites, which only monitored SO₂, were shutdown, since they were well below the federal (NAAQS) and are represented by other monitors in the network:
 - o **Lawrenceville (54-029-0015)**– last single-point quality control check July 6, 2023
 - o **New Cumberland (54-029-0007)**– last single-point quality control check July 6, 2023
 - o **McKim Ridge (054-009-0007)**– last single-point quality control check January 4, 2024

On June 28, 2023, EPA Region 3 approved the discontinuation of the non-SIP related SO₂ monitors in Hancock County: **Lawrenceville (54-029-0015)** and **New Cumberland/ (54-029-0007)**.

On January 8, 2024, EPA Region 3 approved the discontinuation of operations of the McKims Ridge SO₂ only site since there are two others in the area to fulfill SO₂ SIP monitoring requirements.

- DAQ plans to consolidate the remaining two air monitoring sites in Brooke County, WV – **Follansbee (54-009-0005)** and **Marland Heights (54-009-0011)**.
 - o These sites are within four (4) air-miles of one another
 - o Consultation with EPA Region 3 indicates this plan is acceptable, pending final advance approval from EPA Region 3 of the consolidated location, once it has been identified.
 - o The remaining SO₂ monitor will fulfill the SO₂ SIP monitoring requirement.
 - o A continuous PM₁₀ monitor will remain in the geographic area through the end of the second 10-year maintenance period of the PM₁₀ SIP in 2026.

West Virginia SO₂
3-Year 99% Daily 1-hour Max Averages (NAAQS = 75 ppb)






Table 1 - Monitoring data for the West Virginia portion of the Steubenville OH-WV area for 2009-2022

AQ5 ID	Site Name	Annual 99th Percentile (ppb)														Design Value (ppb)											
		2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2009-2011	2010-2012	2011-2013	2012-2014	2013-2015	2014-2016	2015-2017	2016-2018	2017-2019	2018-2020	2019-2021	2020-2022
Brooke County Monitors																											
54-009-0005	Follansbee	82	131	143	71	49	33	49	33	28	48	34	38	41	30	119	115	88	51	44	38	37	36	37	40	38	36
54-009-0007	McKim Ridge	81	92	75	71	31	32	26	39	23	24	36	41	52	21	83	79	59	45	30	32	29	29	28	34	43	38
54-009-0011	Marland Heights	143	143	235	117	62	48	35	49	27	35	75	39	61	24	174	165	138	76	48	44	37	37	46	50	58	41
Hancock County Monitors																											
54-029-0007	New Cumberland	113	50	36	34	23	29	27	48	17	22	16	20	23	15	66	40	31	29	26	35	31	29	18	19	20	19
54-029-0009	Summit Circle	131	68	66	44	22	26	19	31	15	18	21	24	15	88	59	44	31	22	25	22	21	18	20	22	20	
54-029-0015	Lawrenceville	102	68	34	27	40	34	30	26	17	16	13	10	12	17	68	43	34	34	35	30	24	20	15	13	12	13
Beech Bottom SIP Monitor																											
54-009-6000	Beech Bottom			46	28	21	20	27	40	27	19	10	18			46	37	32	23	23	29	31	29	19	16		
			Less than 75% data capture in at least one quarter																								

Source: U.S. EPA Air Quality System (AQ5)

Table 2 - Monitoring data for the Steubenville OH-WV SIP area for 2009-2022

AQ5 ID	Site Name	Annual 99th Percentile (ppb)														Design Value (ppb)											
		2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2009-2011	2010-2012	2011-2013	2012-2014	2013-2015	2014-2016	2015-2017	2016-2018	2017-2019	2018-2020	2019-2021	2020-2022
Brooke County Monitors																											
54-009-0005	Follansbee	82	131	143	71	49	33	49	33	28	48	34	38	41	30	119	115	88	51	44	38	37	36	37	40	38	36
54-009-0007	McKim Ridge	81	92	75	71	31	32	26	39	23	24	36	41	52	21	83	79	59	45	30	32	29	29	28	34	43	38
54-009-0011	Marland Heights	143	143	235	117	62	48	35	49	27	35	75	39	61	24	174	165	138	76	48	44	37	37	46	50	58	41
Ohio EPA Monitors																											
39-081-0017	Logan St	85	127	114	92	37	30	29	27	18	34	32	22	94	36	109	111	81	53	32	29	25	26	28	29	49	51
39-081-0018	Cardinal, Brilliant			55	37	52	38	50	31	34	9	5	2			55	46	48	42	47	40	38	25	16	5		
39-081-0020	Self Storage			43	28	33	24	23	20	13	8	12	12			43	36	35	28	27	22	19	14	11	11		
54-009-6000	Beech Bottom			46	28	21	20	27	40	27	19	10	18			46	37	32	23	23	29	31	29	19	16		
			Less than 75% data capture in at least one quarter																								

Source: U.S. EPA Air Quality System (AQ5)